

Rippers

SS ripper enables you to do a lot of hard work with minimum effort. Ideal for breaking up hard ground, ripping up stumps or rocks, planting trees, laying polythene pipe or removing rabbit warrens

Reversible point 225x75x16mm

FIRP350: 100x25 billet

FIRP500: 150x32 billet

FIRP700: 150x50 billet

3 point hitch

Model No.	Max Working	Hitch	Recommend Tractor	Approx. weight
FIRP350	350mm	Cat 0 / Cat I	upto 40hp	40kgs
FIRP500	500mm	Cat I / Cat II	25-70hp	72kgs
FIRP700	700mm	Cat II	60hp above	100kgs



Height adjustable ripper

3 point, Cat 1 hitch

Recommended for tractors with less than 50HP



Ripper - Pipelaying

FIRP350PL

FIRP500PL

FIRP700PL

Item Number	WORKING WIDTH (mm)	RIPPING DEPTH (mm)
FIRP4	1200	200
FIRP5	1520	200
FIRP6	1830	200

Cultivators

SS single row "C" tine cultivator is the perfect cultivation tool for the small farm or backyard garden

Heat-treated spring steel rigid shanks wont twist or turn

Working width: 57"

Heavy duty angle frame

Hitch type: 3 point

Category: 0&1

Tractor HP: 18-30HP

Model No.	Number of Shank	Recommend Tractor	Approx. weight
FICULT	6pcs	15-45hp	47 / 49kgs



S Cultivator

The 2" square frames are reinforced & equipped with heavy S-tines for reliable performance

Point hitch

Reversible points

6 1/2" spacing

S-tines 3/8" x 1-1/4" x 16" clearance



Item Number	HP Rating
FISC4	15 to 25
FISC5	15 to 32
FISC6	17 to 40

Subsoilers

Single Shank



#FISH100

Ideal for ripping terrain

Equipped with one fixed shank, fuse bolt is standard spaced shanks

Hassle-free replacement of wearable points

Shank width: 32mm

Max penetration: 457mm

Work depthness: 355mm

Hitch: 3 point cat I & II

Min tractor hp required: 40hp

Three Shanks



#FISH300

Ideal for ripping terrain

Equipped with widely spaced shanks (fixed or adjustable positions)

Shank width: 32mm

Number of shank positions: Variable positions

Max penetration: 457mm

Work depthness: 355mm

Hitch: 3 point cat II

Min tractor hp required: 90hp

COMING SOON