TYRE CHANGERS

Automotive Products

#VP8270

All steel construction 15 3/8" x 18½" base 71/2" diameter x 3/16" thick wheel rest plate Weight: 19kg

Mounts and demounts a full range of tyres from 8" to light truck

To order with motorcycle tyrechanger attachment please order #VP8270MB





Electronic Wheel Balancer #VP827WB

Electronic wheel balancer

10-second cycle time, self-calibration function, gram/ounce/millimetre/inch secretions 143lbs max shaft capacity allows operator to balance most passenger & light truck wheels, 800mm max litre diameter capacity, auto start when hood is lowered Automatic brake, readout for top position weight locator & inside outside measurements, rim width capacity 38mm to 508mm nm

Diameter capacity 254mm to 609mm Item size: L 1199 x W 719 x H 1179 mm

Semi Automatic Tyre Changers

#VP827TC1 Semi automatic tyre changer

For rims up to 330mm wide, 508mm diameter

Turntable rotation torque: 361kgs

Bead breaker with 2500kg force, rim diameter: 254mm-508mm

Wheel width: 330mm max, external locking rim dimensions: 254-457mm

Internal locking rim dimensions: 304-508mm, motor: 240V, 10.5 amp

Single phase: 1740rpm, working pressure: 110PSI

Item size: L 959 x W 749 x H 979 mm

#VP827TC2

Semi automatic tyre changer

Handles tyre sizes up to 965mm diameter x 330mm wide

Includes storage box, an inflation system, air pressure regulator/gauge, and air tank For rims up to 330mm wide, 508mm diameter, turntable rotation torque: 795lbs

Bead breaker with 2500kg force, rim diameter: 254-508mm

Max wheel width: 330mm max, external rocking rim dimensions: 254-457mm Internal rocking rim dimensions: 304-508mm, motor: 240V, single phase: 1740rpm,

Working pressure: 110PSI

Item size: L 1149 x W 749 x H 979 mm



