Procureit Australia Pty Ltd Ph +61 7 3314 2808 F +61 7 3314 2321 e sales@procureit.com.au

PUMPS

<u>12 Volt Diesel & Oil Pump</u> 240 Volt Diesel & Oil Pump



12 volt Diesel & Oil Pump

PETROL DRIVEN

CHEMICAL PUMI

#QWCP552

5.5HP Max suction: 8m Max capacity: 600L/min Total head: 32m Starting system: recoil starting Fuel tank capacity: 3.6L Oil capacity: 0.6L Dry weight: 24Kg Dimensions: 510x370x430mm For all chemicals including sulphuric acid, diesel, oil etc.

Firefighting Kit



#QWFKIT 20 metres 3/4" hose fitted with nozzle & tail fitting 5 metres 2" suction hose with filter & tail

Petrol & Diesel Engine Products

#QDOP12V

Voltage: 12V/24V DC Rated power: 180W/400W Max curent: 15A/17A Max speed: 1400rpm/2400rpm Dia of pipe: 3/4" Length of cable: 1.5m Length of output pipe: 4m Max pump rate: 40L/min

#QDOP240V

Voltage: 240V/50Hz AC Rated power: 600W Max curent: 36A Max pump rate: 60L/min Max speed: 2800rpm Dia of pipe: 1" Length of input pipe: 2m Length of output pipe: 4m

Trash Pump

#QWTP653

Inlet & Outlet Inside dia: 80mm Nut & tail supplied take 75mm hose Hose size: 75mm Pump lift: 26mm Suction height: 7m Max. Pump output: 78m3/hr Engine type: Air cooled, 4 stroke, single Displacement: 196cc Max. Power output: 6.5HP/3600rpm Start type: recoil Con. Operating hours: 2.5hr Fuel tank capacity: 3.6L

Firefighting Pump



Model	QWPF652 (6.5HP)
Suction	38mm (1½ in)
Discharge	1-1/2" + 2 x 1"
port dia.	
Max. head	55m
Мах. сар.	30M3/hr
Max suction	8m
head	
Self-priming	30 S/4m
time	

June-Aug 2009

PAGE 110 REFER

REFER TO PRICELIST - Part Nos. In Alphabetical order