

14" Portable Brick Machine With or Without Stand

Oddbods



#BCM100

Voltage: 240V
Input power: 1650W
No-load speed: 3500r/min
Max cutting dia: 355mm
Max cutting depth: 127mm
Max cutting length: 255W x 406Lmm
NOT SUPPLIED WITH BLADES

#BCM100S

With Stand

#BCM100S to be ordered separately

Mobile Aluminium Scaffolding Tower

#ALHDSCAF

Overall Height: 4.8m

Approved to Australian Standards
number AS/NZS1576.3

Consists of:

- 1.25 x 1.6 ladder frame x 2
- 1.25 x 2.0 ladder frame x 2
- 1.25 x 1.0 guail rail frame x 2
- Bottom brace (black clip) 2791mm x 1
- Diagonal brace (red clip) 2620mm x 10
- Horizontal brace (dark green clip) 2495mm x 6
- Skidproof deck without hatch 2495x540mm x 1
- Skidproof deck with hatch 2495x540mm x 1
- 6" adjustable caster with thread stem x 4
- 4.8mm alum ladder x 1
- 1034mm ladder bracket x 1
- 2442 x 1166mm alum toe board (set) x 1
- Stabilizer x 4
- L 2.5 x W 1.25 x H4.8m

1.98m Aluminium Scaffolding

Capacity: 235kg

Overall dimension: 1970mmL x 740mmW x 1980H

N.W.: 36.9kg



#ALUMSCA

Interior Scaffolder

Capacity: 455kg

Overall dimensions: L185 x W75 x H180cm

N.W.: 58kg



#INTSCA

**REFER TO PRICELIST -
Part Nos. In Alphabetical order**