

3 Point Scoop

Ideal to move sand, soil, gravel etc using the tractor linkages.
 Allows some earthworks without the expense of a front end loader.

Reinforced tubular steel frame

Carbon steel cutting edge

Centre-mounted frame bushing

Spring loaded latch locks, lifts, dumps & resets all from the tractor seat

Suits most compact tractors 20-45hp



Model	Bucket width	Approx. Capacity	Recommend Tractor	Approx. Weight
#FISCOOP24	24"	9 cuft	20-40HP	60/73kgs
#FISCOOP30	30"	6 cuft	25-45HP	81/95kgs

3 Point Cement Mixer

Internal paddles for uniform mixing

17.5" drum opening

32" overall drum length

11-gauge steel drum

540rpm PTO speed

5 cu. Ft. Capacity



Model	Drive ratio	Capacity	Recommend Tractor	Approx. Weight
#FICM5	8.77:1	5 cuft	25HP & above	107/143kgs

Rotary Tiller

All models feature curved or "L" blades

Depth adjustment on skids

A rear deflector keeps soil & debris beneath the tiller for thorough pulverization

Supplied complete with drive shaft, pins & all safety covers

Suits most tractors

Model	#FIRT95L	#FIRT105L	#FIRT125L
Speed of PTO	540rpm		
Working width	950mm	1050mm	1250mm
Working depth	80-120mm		
Speed of cultivator shaft	210rpm		
Blades	16pcs	20pcs	28pcs
Recommended Tractor HP	15-25hp	20-25hp	25-30hp
Approx. Weight	108/140kg	118/152kgs	138/172kg

