

# Carry-Alls



Carry all platform for rear of tractor  
 Suits most compact tractors generally up to 35HP  
 Category 1-3 point linkage  
 760mm high, 600mm wide, forks are 940mm long  
 Load cap: 225kg



Model No.	Capacity	Approx. weight
FICA500	225kgs	26 / 28kgs

Carry all platform for rear of tractor  
 Suits most compact tractors generally up to 45HP  
 Category 1-3 point linkage  
 Load cap: 360kg



Model No.	Capacity	Approx. weight
FICA800	360kgs	45 / 50kgs

Carry all platform for rear of tractor  
 Suits most compact tractors generally up to 50HP  
 Category 1-3 point linkage  
 Hardwood Not Included



Model No.	FICA1200	FICA1500	FICA1800
Plate Size	1200 x 929mm	1500 x 929mm	1800 x 929mm
Loading Capacity	1000kgs	1000kgs	1000kgs
Approx. weight	68kgs	75kgs	82 kgs

# Bale Spears

Features tapered heat treated steel spears designed for hard centre bales allowing easy penetration & withdrawal  
 Main spear length 965mm, two short spears 317mm  
 Cat I & II 3 point hitch  
 Recommended tractor 25HP above



Model No.	Capacity	Approx. weight
FIBS1500E	675kgs	46 / 54kgs

Features tapered heat treated steel spears designed for hard centre bales allowing easy penetration & withdrawal  
 Main spear length 965mm, two short spears 317mm  
 Cat I & II 3 point hitch  
 Recommended tractor 25HP above



Model No.	Capacity	Approx. weight
FIBS1500HD	675kgs	50 / 54kgs

Features tapered heat treated steel spears designed for hard centre bales allowing easy penetration & withdrawal  
 Main spear length 965mm, two short spears 317mm  
 Cat I & II 3 point hitch  
 Recommended tractor 25HP above



Model No.	Capacity	Approx. weight
FIBS1100	500kgs	54 / 60kgs