

Rotary Mower



These economical machines are ideal for the owner to handle their land maintenance requirements

The rotary cutters are designed for dependable service & easy operation
 Protection by incorporating a "stump-jumper" as standard equipment & shear pin PTO driveline

Rear mounted chain-guard as standard equipment & front mounted chain-guard for option.



Model No.	FIRM4	FIRM5	FIRM6
Cutting Width	1200mm	1500mm	1800mm
Cutting Height	40-250mm	40-250mm	40-250mm
PTO speed	540rpm		
Gearbox	1:1.93	1:1.93	1:1.46
Recommended Tractor HP	15hp to 30hp	25hp to 45hp	40hp to 75hp
3PT Hitch	Cat I	Cat I	Cat I
Deck Thickness	2.5mm	2.5mm	3.0mm
Approx. weight	164 / 187 kgs	195 / 241 kgs	264 / 316 kgs

Finish Mower

The wide rear discharge throat for clipping discharge

Greaseable blade spindle

Quick coupler PTO

Four solid wheels for easy height adjustment, & allow the deck to float with the ground contour

The solid wheels are not affected by punctures, ensuring level cut every time

Model No.	FIFM5	FIFM6
Cutting Width	1500mm	1800mm
Cutting Height	35-115mm	35-115mm
Transmission	twin V belt	twin V belt
Gearbox	1:2.83	1:2.83
Recommended Tractor HP	20-50hp	22-50hp
3PT Hitch	Flotation Style, Cat I	Flotation Style, Cat I
Deck Thickness	3.0mm	4.0mm
Approx. weight	144 / 190 kgs	198 / 250 kgs



Box Blade

Ideal to level undulating ground. The rippers breaking up the soil & the following behind blade to level off

Reversible high-carbon steel edge

Height adjustable rippers

3 point, Cat 1 hitch

Recommended for tractors with less than 50hp



Model No.	FIBB5	FIBB6
Number of Rippers	5pcs	6pcs
Working Height	25-100mm	25-100mm
Approx. weight	169 / 196	196 / 225 kgs