

Farm Implements

Garden Shredder & Vacuum Cleaner

#FI650VSC

Two forward speeds, 2-5km/h

Two reverse speeds, 2km/h

Vacuums a 24" path

Max chipping cap: 3"

Blade revolution speed: 900r/min

Engine specifications:

4-stroke, single cylinder, air-cooled

Rated speed: 3600r/min

Rated power: 6.5HP/3600r/min

Fuel tank cap: 0.6L

Oil tank cap: 3.6L

Fuel consumption: <=395/kw.h

Starting mode: recoil start



PRICED TO CLEAR

Mower

#LM650



PRICED TO CLEAR

Power: 6.5HP petrol engine

Overall dimensions: 1500Lx900Wx920Hmm

Shears the stubble: 3-8cm

Tillage width: 80cm

Production rate: 1000-2000 m/hour

Weight: 82kg

Extra Heavy Duty Post Driver

#HHPDHD



Slashers

#SM120

Cutting width: 1.15m

Cutting height (with adjust skids): 25-100mm

Tractor HP: 20-35HP

Tractor connection 3 point linkage

Gearbox/PTO speed: 540rpm

Control depth by skids

Overall dimension: 1.42L x 1.46W x 0.47Hm



#SM1300

Tractor HP: 20-40HP

Tractor connection 3 point linkage

Gearbox/PTO speed: 540rpm

2 blades for grass cutting

Control depth by skids

Front rubber protector

#SM135

Cutting width: 1.35m

Cutting height (with adjust skids): 25-100mm

Tractor HP: 25-45HP

Tractor connection 3 point linkage

Gearbox/PTO speed: 540rpm

Control depth by skids

Overall dimension: 1.42L x 1.46W x 0.47Hm

#SM1500-40

Tractor HP: 40HP

Tractor connection 3 point linkage

Gearbox/PTO speed: 540rpm

2 blades for grass cutting

Control depth by skids

Front rubber protector

#SM150

Cutting width: 1.45m

Cutting height (with adjust skids): 25-100mm

Tractor HP: 25-50HP

Tractor connection 3 point linkage

Gearbox/PTO speed: 540rpm

Control depth by skids

Overall dimension: 1.53L x 1.56W x 0.47Hm

#SM1500-65

Tractor HP: 65HP

Tractor connection 3 point linkage

Gearbox/PTO speed: 540rpm

2 blades for grass cutting

Control depth by skids

Front rubber protector